

Konica Minolta bizhub 423/363/283/223 Specification & Installation Guide



KONICA MINOLTA

5/2010

bizhub 423/363/283/223 Specifications

Basic

Type Printer/Copier/Scanner Desktop/
Free-Standing

Continuous Copy/Print Speeds:

Simplex (ppm): 8.5" x 11" (Letter)

Media Type/Tray	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper/1st	42	36.5	28.5	22.5
Plain Paper/2nd	41.9	36.5	28.5	22.5
Plain Paper/3rd	41	36.5	28.5	22.5
Plain Paper/4th	41	36.5	28.5	22.5
Plain Paper/LCT	41	36.5	28.5	22.5
Plain Paper/Bypass	41	36.5	28.5	22.5
Thick 1/Bypass*	13	12.5	10	9
Thick 2/Bypass*	13	12.5	10	9

Duplex (ppm): 8.5" x 11" (Letter)

Media Type/Tray	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper/1st	41.5	36.5	28.5	23
Plain Paper/2nd	41.5	36.5	28.5	23
Plain Paper/3rd	41	36.5	28.5	23
Plain Paper/4th	41	36.5	28.5	23
Plain Paper/LCT	41.5	36.5	28.5	23
Plain Paper/Bypass	41.5	36.5	28.5	23

Simplex (ppm) 8.5" x 14" (Legal)

Media Type/Tray	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper/1st	25	23.5	18.5	16
Plain Paper/2nd	25	23.5	18.5	16
Plain Paper/3rd	25	23	18.5	16
Plain Paper/4th	25	23	18.5	16
Plain Paper/Bypass	25	23.5	18.5	16
Thick 1/Bypass*	10.5	10	8	7.5
Thick 2/Bypass*	10.5	10	8	7.5

Simplex (ppm) 11" x 17" (Ledger)

Media Type/Tray	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper/1st	21	20	16	14
Plain Paper/2nd	21	20	16	14
Plain Paper/3rd	21	20	16	14
Plain Paper/4th	21	20	16	14
Plain Paper/Bypass	21	20	16	14
Thick 1/Bypass*	10	9.5	7.5	7
Thick 2/Bypass*	10	9.5	7.5	7

*Thick Paper only from Bypass

Document holder	Stationary (mirror scanning)
Photoconductor	OPC
Luminous source	White fluorescent lamp
Copying System	Laser electrostatic copy method
Developing System	Dry-type dual-component HMT developing method
Fusing System	Roller Fusing System
Resolution	Scanning: 600 x 600 dpi Printing: 1800 (equivalent) x 600 dpi
Monthly Duty Cycle	bizhub 423: 150,000 bizhub 363: 150,000 bizhub 283: 120,000 bizhub 223: 60,000 Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approached duty cycle on continual basis.

Copy

Originals	Types: Sheets, books (page spreads), three-dimensional objects Size: Maximum 11" x 17" Weight: 4.5 lb. (three-dimensional objects)
Copy Sizes	1st and 2nd Tray: 5.5" x 7.16" to 11.69" x 17" (140 x 182 mm to A3) Bypass Tray: 3.54" x 5.5" to 11.69" x 17" (90 x 140 mm to A3)
Storable number of Pages	Max number for electronic sorting (incl. Fax, Print, Copy): 3000 pages
Warm-up time	bizhub 423/363: ≤ 30 seconds bizhub 283/223: ≤ 30 seconds with HDD ≤ 25 seconds without HDD (at room temperature/ 73.4°F/65%RH)
Image loss width	Printing: Leading edge: 0.165" (4.2 mm) Trailing edge: 0.118" (3 mm) Rear edge: 0.118" (3 mm) Front edge: 0.118" (3 mm) Copying: All edges: 0.165" (4.2 mm)

First Copy
Output Time

From Platen: 8.5" x 11" (Letter) (seconds)

	bizhub 423/363	bizhub 283/223
Plain Paper	≤ 3.6	≤ 4.2

From RADF: 8.5" x 11" (Letter) (seconds)

Original/Copy Mode	bizhub 423/363	bizhub 283/223
Simplex/Simplex	≤ 8.3	≤ 10.6
Simplex/Duplex	≤ 14	≤ 18
Duplex/Simplex	≤ 13	≤ 17
Duplex/Duplex	≤ 15	≤ 19

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



KONICA MINOLTA

Copy continued

Copy Productivity

1:1 Copy Speed: 8.5" x 11" (Letter) (ppm)

	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper	42	36	28	22
Thick Paper	13	12.5	10	9

Sort/Staple (Simplex): 8.5" x 11" (Letter) (ppm)

	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper	42	36	28	22
Thick Paper	13	12.5	10	0

Punch (Simplex): 8.5" x 11" (Letter) (ppm)

	bizhub 423	bizhub 363	bizhub 283	bizhub 223
Plain Paper	42	36	28	22
Thick Paper	13	12.5	10	9

Originals per Minute 42 opm @ 600 dpi, Letter
(opm during copy)

Magnification Ratios Fixed Zoom Ratios:
Enlarge: 121.4%, 129.4%, 154.5%, 200%
Reduce: 78.5%, 77.2%, 64.7%, 50.0%
Free Scale:
Variable Range: 25%-400% (0.1 increments)

Multiple Copies 1 – 9,999

Density Control Copy density adjustment [Manual 9 levels]
Background adjustments [Manual 9 levels/
Auto] Text Enhancement/Adjustments

Copy Function

- Electronic sort/Criss Cross
- Multi job (Priority: for manual, for copy, for 1-set first output, for security documents)
- Multi task functionality (some combinations are restricted)
- Illegal Copy prevention (Detection system)
- LDAP, PSDA support
- Power save (Sleep/Low Power mode)
- Help/Universal Design/Display magnification/Contrast adjustments /
- Sharpness/Exposure
- ID/Program/Setting menu/Counter/ Setting content confirmation
- Auto Copy Start/Proof copy/Interrupt/ Auto-reset
- Hidden mark copy, Hidden mark detection (Copy guard, Password copy)
- Filing number (when HDD installed)
- Base color, Negative-Positive Reverse, Mirror Image, Multi-page
- Enlargement, Image repeat, Fixed shape repeat

Print Controller

Type

Standard:

Emperon Print Controller with:

- 3rd Generation Unified Firmware
- bizhub Extended Solutions Technology (OpenAPI)
- Direct printing of PDF or TIFF data
- HDD data backup function (when HDD installed)

Processor Speed MPC8533E/667 MHz

Memory Main Memory: 2 GB (shared print, copy, scan and fax memory)
SSD: 1 GB (including System Area)

Hard Disk Drive HD-516 250 GB Hard Disk Drive
bizhub 423/363: Standard
bizhub 283/223: Option

Print Resolution 1800 dpi (equivalent) x 600 dpi

Interface 10 Base-T/100 Base-TX/1000 Base-T,
USB 1.1, USB 2.0, USB Host

Grayscale Gradations 256 shades

Page Description Language PCL5e/c Emulation, PCL XL ver.3.0
Emulation, PostScript 3 Emulation (3016),
XPS v1.0 (XML Paper Specification)

Protocols TCP/IP (IPv4/IPv6), BOOTP, ARP, ICMP,
DHCP, DHCPv6, AutoIP, SLP, SNMP,
FTP, LPR/LPD, RAW Socket, SMB, IPP,
HTTP, POP, SMTP, LDAP, NTP, SSL,
IPX/SPX, AppleTalk, Bonjour, NetBEUI,
WebDAV, DPWS, S/MIME, IPsec, DNS,
Dynamic DNS, LLNMR, LLTD

Supported OS

Server:

- Windows 2000 Server/2003 Server/2008 Server R2
- Windows 2003 Server/2008 Server R2 x64 Edition

Client:

- Windows 2000/XP/Vista/7
- Windows XP/Vista/7 x64bit Edition
- Windows 2003 Server/2008 Server
- Windows 2003 Server/2008 Server /2008 Server R2 x64bit Edition
- Macintosh OS 9.2, OS X ver 10.2, Intel OS X 10.4 or later
- Red Hat Enterprise Linux

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



KONICA MINOLTA

Printer Drivers	<p>PCL6: Printer Driver for:</p> <ul style="list-style-type: none"> • Windows 2000/XP • Windows 2003 Server/ 2003 Server R2/Vista/7/2008 Server • Windows XP/2003 Server/2003 Server R2/Vista/2008 Server/2008 Server R2 x64 Edition <p>PS3: Printer Driver for:</p> <ul style="list-style-type: none"> • Windows 2000/XP PS • Windows 2003 Server/2003 Server R2/ Vista/2008 Server/ 2008 Server R2 PS • Windows XP/2003 Server/Vista/ 2008 Server x64 Edition • Macintosh OS 9.2 or later PPD Printer Driver • Macintosh OS X 10.2 or later PPD+PDE Printer Driver • Macintosh OS X Intel 10.4 or later PPD+PDE Printer Driver • PPD file for Red Hat Enterprise Linux (CUPS v1.1.22) Printer Driver <p>XPS: Printer Driver for:</p> <ul style="list-style-type: none"> • Windows Vista/7/Server 2008 XPS Driver • Windows Vista/7/Server 2008/ Server 2008 R2 x64 Edition XPS Driver 	Print Driver Features	<p>Basic Functions:</p> <ul style="list-style-type: none"> • Number of Prints: 1 – 9999 • Direction • Paper Tray: APS (Auto Paper Select Mode), Tray Selection (Tray 1 – 4/Multi bypass/LCT) • Output Tray: Top output bin • Zoom: Auto zoom/Free Scaling: 25 – 400% • Original image type: Document/Photo/ DTP/WEB/CAD • Image Adjustment: Simple Settings/ Detail Settings <p>Finishing (when appropriate finisher is configured):</p> <ul style="list-style-type: none"> • Collate (On/Off) • Offset (On/Off) • Binding Position setting • Auto/Left Bind/Top Bind/Right Bind • Punch (On/Off) Linked with Binding Position setting. (2 holes/3 holes selectable) • Staple (Corner/2 Position (Left)/ 2 Position (Right)/2 Position (Top)) (Off/1 Position/2 Position), Linked with Binding Position setting. • Center Staple and Fold, Half-Fold <p>Layout Settings:</p> <ul style="list-style-type: none"> • 1-Sided • 2-Sided • Combination (2-in-1, 4-in-1, 6-in-1, 9-in-1, 16-in-1) • Order (Horiz. Asc./Horiz. Desc./ Vert. Asc./Vert. Desc.) • Border Line (ON/OFF), Border (None/ Frame/Line) • Booklet printing • Skip Blank Pages <p>Print Settings:</p> <ul style="list-style-type: none"> • Cover Mode, Transparency Interleave, Chapter, Account Track, User Authentication, Watermark, Overlay, Per Page Setting, PC-Fax, Secure Print (HDD necessary), Proof Print, Save in User Box, Copy Protect, Date/Time, Page Number, Header/Footer
Fax Driver (Requires FK-508 Fax Kit)	<p>Server:</p> <ul style="list-style-type: none"> • Windows 2000 Server/2003 Server/ 2008 Server R2 • Windows 2003 Server/2008 Server R2 x64 Edition <p>Client:</p> <ul style="list-style-type: none"> • Windows 2000/XP/Vista/7 • Windows XP/Vista/7 x64bit Edition • Windows 2003 Server/2008 Server • Windows 2003 Server/2008 Server/ 2008 Server R2 x64bit Edition 		
MetaFrame Operating Environment	<p>The operation of this driver has been confirmed only in the following environments:</p> <p>Server OS: Windows 2000 Advanced server/ Windows 2003 Enterprise Server</p> <p>MetaFrame: Citrix® MetaFrame® Presentation Server 3.0 Citrix® MetaFrame® Presentation Server 4.0</p> <p>Client OS: Windows 2000/Windows XP</p> <p>ICA Client: ICA 32bit</p>	Resident Fonts	<p>PCL: Western Type: 80 outline + Japanese fonts</p> <p>PS3 Emulation: Western Type1 font: 137 outline + Japanese fonts</p>
		Print Features	Encrypted Network Password Printing, Job Skip, MyTab Driver Feature, Print from USB Memory

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



KONICA MINOLTA

Scan

Scan Speed with DF-621	Color/B&W: 70 opm (@ 300 dpi, letter), 42 opm (@ 600 dpi, letter)
Scan Size Original	Platen scan: Max. 11.69" x 17" (297 mm x 431.8 mm) (A3 or WLTR) ADF scan: Max. 11.69" x 39.37" (297 mm x 1000 mm) (400 dpi or less) Max. 11.69" x 17" (297 mm x 432 mm) (600 dpi)
Scan Modes	Color Mode: Auto Color, Full Color, Gray Scale, Black Background Removal: Auto/Manual Original Type selections: Text, Text/Photo, Photo, Copied Paper, Dot Matrix Original
Scan Resolution	Push: 200/300/400/600 dpi Pull: 100/200/300/400/600 dpi
Scan File Formats	TIFF, PDF, Compact PDF, JPEG, XPS, Compact XPS
Scan Features	bizhub Send, Separate Scan, Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan-to-User Box, Scan-to-USB Memory*, Network TWAIN (via Ethernet TCP/IP), Scan-to-Me and Scan-to-Home, Scan-to-WebDAV *Requires HD-516
Interface	Ethernet 10Base-T/100Base-TX/1000Base-T
Supported OS	NT4.0 SP6/Windows 2000/XP/Vista/Mac OS
Scan Drivers	TWAIN Driver - Real Time Mode (Push/Pull) TWAIN Driver - Real Time Mode (Non-GUI version for eCopy ScanStation and RightFAX) HDD TWAIN Driver - (Scan-in-User box, then use HDD-TWAIN driver to retrieve files)

Fax

Fax	Standard: Internet Fax (Color*/B&W) (Requires HD-516) Option: FK-508 Includes Super G3 Fax (B&W), IP Address Fax** (Color*/B&W), PC Network Fax Driver (B&W) *Color send only. **Requires HD-516.
Fax Line/Mode	PSTN (Public Switch Telephone Network), PBX (Private Branch Exchange), Super G3 (Fax line)
Scan Line Density	G3 (8 dot/mm x 3.85 line/mm - 600 x 600 dpi)
Baud Rate	2.4 - 33.6 kbps
Fax Transmission Speed	Approx. 3 sec (A4, V.34, 33.6 kbps, JBIG)
Encoding	MH, MR, MMR, JBIG
Communication Mode	ECM/G3
Color Support	No
Fax Features	Program, Select from address book, Group dial program, Temporary one-touch dial, Auto redial, Original type (text, text/photo, photo, Dot matrix), Density, Memory/Quick TX, Busy/error redial, Broadcast TX, Priority TX, Timer TX, Confidential TX/RX, Relay TX request, Polling TX/RX, Bulletin, 2-in-1 TX, Original bind direction/Paper bind direction, Frame Erase TX, TX Original size setting, Mixed original TX, Rotation TX, Overseas TX, ECM OFF, V34 OFF TX, Password TX, Memory RX, Memory vicarious execution RX, Password RX, Call Rejection, 2-in-1 RX, Rotation RX, 2-Sided RX, Confidential print, Relay broadcast, Auto Reduction print, Full size print, TEL/FAX Auto switch, Audio response, Answering Machine Connection, Number display, Dial-in, vicarious execution forward, Remote RX, Nighttime Receiving User Box destination setting, Activity report, TX Result Report, Broadcast Result TX Report, Broadcast Result RX Report, Polling timer reservation TX Report, Sequential polling timer reservation TX Report, Confidential RX report, Bulletin TX report, Various lists, 2-in-1 record, 2-Sided record, Long paper original TX/RX, PC-FAX TX/RX, Revival TX, TSI routing, Box support (Save/Email forward), Mistake TX prevention, 2 line support

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



KONICA MINOLTA

Paper Handling

Paper Input	DF-621 Reversing Automatic Document Feeder bizhub 423/363: Standard bizhub 283/223: Option OC-509 Original Cover bizhub 283/223: Option
Paper Trays	Standard: Tray 1 Capacity/Paper Size/Paper Weight: 500-sheet/ 5.5" x 7.16" to 11.69" x 17" (140 x 182 mm to A3)/16 lb. bond to 24 lb. (60-90 g/m ²) Tray 2 Capacity/Paper Size/Paper Weight: 500-sheet/ 5.5" x 7.16" to 11.69" x 17" (140 x 182 mm to A3)/16 lb. bond to 24 lb. (60-90 g/m ²) Bypass Tray Capacity/Paper Size/ Paper Weight: 150-sheet/3.54" x 5.5" to 11.69" x 17" (90 x 140 mm to A3)/16 lb. to 55.75 lb. (60-210 g/m ²) Optional: PC-109 Paper Feed Cabinet Capacity/ Paper Size/Paper Weight: 500-sheet/ 5.5" x 7.16" to 11.69" x 17" (140 x 182 mm to A3)/16 lb. bond to 24 lb. (60-90 g/m ²) PC-208 Paper Feed Cabinet Capacity/ Paper Size/Paper Weight: 2 x 500-sheet/ 5.5" x 7.16" to 11.69" x 17" (140 x 182 mm to A3)/16 lb. bond to 24 lb. (60-90 g/m ²) PC-409 Large Capacity Cabinet Capacity/Paper Size/Paper Weight: 2,500-sheet/ 8.5" x 11" (A4) (portrait only)/ 16 lb. bond to 24 lb. (60-90 g/m ²)
Maximum Paper Capacity	3,650 sheet (total with options)
Supported Media Types	Plain Paper: (16 lb. to 24 lb.) (60-90 g/m ²) Thick Paper 1*: (24.25 lb. to 40 lb.) (91-150 g/m ²) Thick Paper 2*: (41 lb. to 55.75 lb.) (151-210 g/m ²) OHP Transparencies*, envelopes*, postcards*, labels* <small>*Can be fed through the bypass tray only</small>
Paper Output	Standard: Inner Output Tray: 250 sheet Capacity Optional: JS-505 Inner Job Separator Inner Output Tray 1: 150 Sheet Capacity Inner Output Tray 2: 50 Sheet Capacity

Finishing

Optional:	FS-527 Floor Finisher - 50-sheet stapling Output Tray 1: 200 Sheet Capacity Output Tray 2: 3,000 Sheet Capacity JS-603 Additional Output Tray for FS-527 Output Tray 3: 100 Sheet Capacity PK-517 Punch Kit for FS-527 2 and 3 Hole Punching, Each Page Hole Punched Individually SD-509 Saddle Stitch Kit for FS-527 - 60-page Booklet Making Output Booklet Tray: 20 Booklets FS-529 Inner Finisher - 50-sheet stapling Output Tray: 300 Sheet Capacity
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

User Box

User Box	bizhub 423/363: Standard
Functionality	bizhub 283/223: Option (Requires HD-516)
Maximum Number of User Boxes	1,000 User Boxes for Document Storage, Re-Output, Distribution
Maximum Document Storage	Up to 200 Documents per User Box, Up to 3,000 Documents in all User Boxes, Up to 10,000 pages in all User Boxes

i-Option

Optional:	UK-203 1 GB Memory Upgrade Kit Required to enable any i-Option, PageScope My Panel Manager LK-101 Enables Web Browsing at Control Panel/ Image Panel to create/combine/route documents LK-102 Enables Enhanced Scanning Security with advanced digital IDs for Encrypted PDF LK-105 Enables scanning to a searchable PDF (OCR)
------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

External Keyboard

Optional:	Keyboard Option KH-101 Keyboard Holder External Keyboard Mounting Kit EK-604 USB Kit Enables USB connection for External Keyboard EK-605 USB Kit Enables USB connection for External Keyboard and Bluetooth Printing
------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Authentication Devices

Optional:

AU-102 Biometric Finger Vein Authentication

AU-201H HID Proximity Card Authentication

AU-202H HID iClass Card Authentication

AU-211P CAC/PIV Card Authentication

WT-506 Working Table
Working Table to support Authentication Devices

Security

Security Features**Standard:**

ID & Print (with HD-516), IEEE 802.1X Authentication, External Server Authentication, NDS Authentication over TCP/IP, Secure Print (with HD-516), Support for SMTP Authentication (POP before SMTP), IP Filtering, Encrypted Communications (SSL, S/MIME, Encrypted PDF)

Optional:

SC-507 Copy Guard Kit
Enables Watermark Security to prevent unauthorized copying of documents and Password Copy Feature

Power

Power Requirements 120V/60Hz @ 12A (120V)

Power Consumption Maximum Consumption: $\leq 1500W$
Low Power Mode Consumption: $\leq 7.6 W$
Sleep Mode Consumption: $\leq 7.6 W$

TEC Value (Wh) bizhub 423: 3,200
(Typical Electricity bizhub 363: 3,030
Consumption bizhub 283: 2,410
of 1 week) bizhub 223: 2,130

Dimensions

Dimensions bizhub 423/363: 24.5" x 31.2" x 32.2"
(WxDxH) bizhub 283/223: 24.5" x 31.2" x 27.6"

Weight bizhub 423/363: 169 lb.
bizhub 283/223: 149 lb.


Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide




KONICA MINOLTA


Space Requirements



bizhub 423/363/283/223 + DF-621 + PC-208 + FS-527 + SD-509



bizhub 423/363/283/223 + DF-621+PC-208+FS-529



bizhub 423/363/283/223 + DF-621+PC-208+JS-505

Konica Minolta bizhub 423/363/283/223


Specification & Installation Guide



Environmental Considerations

Temperature		50° F to 86 F°
Humidity		15% to 85%
Acoustic Noise	Sound Levels while engine under operation:	bizhub 423 ≤ 70.8 dB
		bizhub 363 ≤ 69.9 dB
		bizhub 283 ≤ 68.7 dB
		bizhub 223 ≤ 67.8 dB
	Sound Levels while engine during idle:	bizhub 423 ≤ 52.0 dB
		bizhub 363 ≤ 52.0 dB
		bizhub 283 ≤ 48.0 dB
		bizhub 223 ≤ 48.0 dB
Ozone emission		1.5 mg/h or less

Electrical Requirements

Line Options	Dedicated	NEMA Diagram for 5-15R 
Voltage:	120V	
Amperage	12 A	
Cycles	60 Hz	
NEMA Part No:	5-15R	
Cord Length	6.0 ft.	

Note: The main electrical outlet must be located within 6.0 feet from the right rear corner of the bizhub 423/363/283/223 main unit.

Konica Minolta bizhub 423/363/283/223


Specification & Installation Guide



KONICA MINOLTA

Component Considerations

Automatic Duplex Unit (Standard)



Support Paper Type	Plain Paper (16 lb. to 24 lb.) (60 g/m ² —90 g/m ²)
Support Paper Size	Width: 5.5" to 11" (139.7 mm to 297 mm), Length: 6.22" to 17" (158 mm to 431.8 mm)
Power Requirements	Supplied from main unit

DF-621 Automatic Document Feeder (Standard: bizhub 423/363; Option: bizhub 283/223)



Type	Reversing Automatic Document Feeder
Support Paper Size	11" x 17" to 5.5" x 8.5"
Support Paper Weight	Single-Sided: 9.31 lb. to 34 lb. bond (35 g/m ² —128 g/m ²) Double-Sided: 13.31 lb. to 34 lb. bond (50 g/m ² —128 g/m ²)
Paper Capacity	Max. 100 sheets (21.25 lb.)
Paper Transfer Speed	Simplex mode: 42/42 ipm (Color/Monochrome) (TBD) (A4-LEF, 8.5" x 11"-LEF) Duplex mode: 22/22 ipm (Color/Monochrome) (A4-LEF, 8.5" x 11"-LEF, compared to simplex: 52%/52% (Color/Monochrome)) Scan simplex mode: 70/70 ipm (Color/Monochrome) (A4-LEF, 8.5" x 11"-LEF, simplex feed 300 dpi) Scan duplex mode: 31/31 ipm (Color/Monochrome) (A4-LEF, 8.5" x 11"-LEF, compared to simplex: 44%/44% (Color/Monochrome))
Power Requirements	Supplied from main unit
Max. Power Consumption	48W or less
Dimensions (WxDxH)	23.44" x 21.31" x 4.56"
Weight	25.38 lb (11.5 kg)

OC-509 Original Cover



Type	Original Cover/Platen Cover
------	-----------------------------

FK-508 Fax Kit



Communication	ECM/Super G3
Compatible Lines	PSTN, PBX/NCC, fax line (G3)
Line Density	G3: R8 x 3.85, R8 x 7.7, R8 x 15.4, R16 x 15.4 (line/mm)
Modem Speed	2.4 kbps – 33.6 kbps
Compression	MH/MR/MMR/JBIG
Sending Paper Size	Max. 11" x 17"
Recording Paper Size	11" x 17" to 5.5" x 8.5"
Transmission Speed	Less than 3 sec. (V.34, JBIG)
Scan Speed	1 sec. (Letter/Fine Mode)

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide




Component Considerations continued

FK-508 Fax Kit continued



Number of Program Dial	400 programs and 10 temporary One-Touch
Number of Group Dial	100 (500 destinations per group)
Sequential Multiple Station Transmission	Max. 600
Other Transmitting Functions	Mixed Original, Frame Erase Transmission, Sharpness, Background Adjustment, Scan Size Select Function, Top/Bottom Correction Function, Memory Transmission, Quick Memory Transmission, Timer Transmission, Incomplete Transmission Hold (Restored Transmission), Manual Transmission, Confidential Transmission, Password Transmission, Polling Transmission, Bulletin Function, Relay Transmission, Email Transmission (File Type Select Function), Fax Forwarding Function, Overseas TX, V.34 OFF, ECM OFF
Other Receiving Functions	Memory Reception, Confidential Reception, Polling Reception, Bulletin Function, Fax Forwarding (to any destination stored in the Address Book), TSI Routing (to any destination stored in the Address Book).

FS-527 Floor Finisher (50 Sheets)



Type	Floor Finisher
Support Paper Type	Output Tray 1 and Output Tray 2: Plain Paper (16 lb. to 24 lb.), Thick Paper (24.19 lb. to 79.81 lb.), OHP transparencies, postcards, envelopes, label sheets, letterhead, color paper Punch Settings: Plain Paper (16 lb. to 24 lb.), Thick Paper 1/2/3 (24.19 lb. to 68.13 lb.) Staple Settings: Plain Paper (16 lb. to 24 lb.), Thick Paper 1/2 (24.19 lb. to 55.63 lb.)* Finishing Tray 3 (Opt.): Plain Paper (16 lb. to 24 lb.) Thick Paper 1/2/3 (24.19 lb. to 68.13 lb.) OHP transparency, envelope, label sheets, letterhead <small>*Can be used only as a Cover Page</small>
Support Paper Size	Output Tray 1: 12.25" x 18", 11" x 17" to 5.5" x 8.5" * Output Tray 2: 12.25" x 18", 11" x 17" to 5.5" x 8.5"* Staple Settings: 11" x 17", 8.5" x 14", 8.5" x 11"
Mode	Group/Sort/Offset Group*/Offset Sort*/Staple* <small>* Fed to output tray 2</small>
Tray Paper Capacity	Output Tray 1: Plain Paper (16 to 24 lb.) 200 sheets Thick Paper 1/2/3/4 (24.19 lb. to 79.81 lb.) OHP transparency, envelope, labels, letterhead: 20 sheets Output Tray 2: Group/Sort/Offset Group/Offset Sort Plain Paper (16 to 24 lb.) 8.5" x 11" 3,000 sheets 8.5" x 14" 1,500 sheets 5.5" x 8.5" 500 sheets Group/Sort Thick Paper 1/2/3/4 (24.19 to 79.81 lb.) OHP transparency, envelope, labels, letterhead: 20 sheets

continued


Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Component Considerations


FS-527 Floor Finisher (50 Sheets) continued



Staple Mode	Plain Paper (16 to 24 lb.): 50 sheets Thick Paper (24.19 to 31.94 lb.): 30 sheets Thick Paper (32.19 to 55.63 lb.) 15 sheets
Staple Capacity	Plain Paper (16 lb. to 24 lb.) 2 to 9 sheets: 100 copies/sets 8.5" x 14" or larger: 50 copies 10-20 sheets: 50 copies/sets 21-30 sheets: 30 copies/sets 31-40 sheets: 25 copies/sets 41-50 sheets: 20 copies/sets
Punch Settings	By optional Punch Kit (PK-517)
Available Options	Saddle Kit (SD-509), 3rd Tray (JS-603)
Power Requirements	Supplied from Main Unit
Max. Power Consumption	56 W or less
Dimensions W x D x H	20.81"(W) x 25.25"(D) x 40.38"(H)
Weight Approx.	92.56 lb. (42 kg)
Consumables	Staples SK-602 (5,000 x 3 pkg/case)

Note: Paper weight, type and size is limited to bizhub 423 Series, although FS-527 may have greater specifications.

SD-509 Saddle Stitcher



Applicable	FS-527 Finisher
Support Paper Weight	15 (16 lb. to 24 lb.) or 14 Sheets (16 lb. to 24 lb.) + 1 Sheet Thick (16 to 55.63 lb.)
Support Paper Type	Center Staple: Plain Paper (16 lb. to 24 lb.) Half-Fold: Plain Paper (16 lb. to 24 lb.)
Support Paper Size	Center Staple & Fold, Half-Fold: 12.25" x 18", 11" x 17", 8.5" x 14", 8.5" x 11"
Max. Number of Sheets that can be Center-Stapled	15 Sheets Plain Paper (16 lb. to 24 lb.) 14 Sheets Plain Paper (17 lb. to 24 lb.) + 1 Sheet Thick (55.63" lb.)
Max. Number of Folded Sheets	Half-Fold: 3 Sheets
Capacity of Folding Output Tray	Plain Paper 21.25 lb. 1 to 3 sheets: 20 copies 4 to 10 sheets: 10 copies 11 to 15 sheets: 5 copies
Power Requirements	Supplied from Finisher FS-527
Dimensions (WxDxH)	9.4"(W) x 22.8"(D) x 21"(H)
Weight	52.9 lb. (24 kg)
Consumables	Staples SK-602 (5,000 x 3 pkg/case)

Note: Paper weight, type and size is limited to bizhub 423 Series, although SD-509 may have greater specifications.


Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Component Considerations continued

PK-517 Punch Kit



Applicable	FS-527
Number of holes	2 or 3 holes
Support Paper Weight	Plain Paper (16 lb. to 24 lb.), Thick Paper 1/2/3 (24.25 lb. to 68.13 lb.)
Support Paper Size	2-Hole Punch Setting: 11" x 17" to 8.5" x 11" 3-Hole Punch Setting 11" x 17" to 8.5" x 11"
Power Requirements	Supplied from Finisher
Dimensions	2.3" (W) x 18.5" (D) x 5.3" (H)
Weight Approx.	Approx. 3.94 lb. (1.8 kg)

FS-529 Inner Finisher (Staple Function only) (50 sheets)



Type	Staple Finisher
Support Paper Type	Plain Paper (16 lb. to 24 lb.), Thick Paper (24.19 lb. to 72.06 lb.) OHP transparency, envelope, label sheets, letterhead.
Support Paper Size	12.25" x 18"; 11" x 17" to 5.5"x 8.5"
Mode	Group, Sort, Offset Group, Offset Sort, Staple
Tray Paper Capacity	Group/Sort/Offset Group/Offset Sort Plain Paper (16 lb. to 24 lb.) 8.5" x 11": 300 sheets; 8.5" x 14": 250 sheets OHP transparency, envelope, label sheet, letterhead: 10 sheets Thick Paper (24.19 lb. to 24 lb.) Group/Sort: 10 sheets Thick Paper (24.19 lb. to 55.94 lb.) Offset Group/Offset Sort: 10 sheets Staple Plain Paper (16 lb. to 24 lb.) 8.5" x 11": 300 sheets (not stapled) or 30 stapled sets (50 pg/set) 8.5" x 14": 250 sheets (not stapled) or 30 stapled sets (50 pg/set)
Staple Mode	Corner Front/Back, 2-point
Max. Number of Stapled Sheets	8.5" x 11" or smaller: 50 sheets 8.5" x 14" or larger: 30 sheets
Power Requirements	Supplied from Main Unit
Max. Power Consumption	56 W or less
Dimensions W x D x H	18.56"(W) x 22.19"(D) x 5.81"(H)
Weight Approx.	26.44 lb. (12 kg)
Consumables	Staples SK-602 (5,000 x 3 pkg/case)

Note: Paper weight, type and size is limited to bizhub 423 Series, although FS-529 may have greater specifications.

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide




Component Considerations

JS-603 Job Separator (3rd Output Tray)



Applicable	FS-527 (Output Tray 3)
Support Paper Weight	Plain Paper (16 lb. to 24 lb.), Thick Paper 1/2/3 (24.25 lb. to 68.13 lb.) OHP transparency, envelope, label sheet, letterhead
Support Paper Size	12.25" x 18", 11" x 17" to 5.5" x 8.5"
Number of Bins	1 Exit Tray
Stacking Capacity	Plain Paper (16 lb. to 24 lb.): 100 sheets, Thick 1/2/3/4 (24.19 lb. to 79.81 lb.) OHP transparency, envelope, label sheet, letterhead: 10 sheets
Power Requirements	Supplied from Finisher
Dimensions	6.5" (W) x 15.3" (D) x 2.5" (H)
Weight Approx.	Approx. 2.19 lb. (1 kg)

JS-505 Job Separator Tray



Number of Bins	2 bins; Output Tray 1, Output Tray 2
Support Paper Type	Output Tray 1: Plain Paper: (16 lb. to 24 lb.) Output Tray 2: Plain Paper: (16 lb. to 24 lb.), Thick Paper (24.19 lb. to 39.88 lb.), Thick Paper 2 (40.19 lb. to 55.63 lb.), Thick Paper 3 (55.88 lb. to 68.13 lb.), Thick Paper 4 (68.38 lb. to 71.31 lb.), OHP transparencies, postcards, label sheets, envelopes, banner paper
Support Paper Size	Output Tray 1: 11" x 17" to 8.5" x 11" Output Tray 2: 12.25" x 18", 11" x 17" to 5.5" x 8.5", postcard
Mode	Sort, Group, Offset Group, Offset Sort
Tray Paper Capacity	Output Tray 1: Plain Paper: (16 lb. to 24 lb.): 50 sheets Output Tray 2: Plain Paper: (16 lb. to 24 lb.): 150 sheets Thick Paper 1/2/3/4 (24.19 lb. to 71.31 lb.), OHP Transparencies, postcards, label sheets: 20 sheets Envelopes: 10 sheets Banner Paper: 1 sheets
Dimensions (W x D x H)	16.63"(W) x 18.75"(D) x 5.13"(H) 21.38"(W) when tray is pulled out
Weight Approx.	11 lb. (5 kg)


Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Component Considerations continued


PC-109 Paper Feed Cassette



Type	1 x 500 sheet universal drawer + storage drawer
Support Paper Type	Plain Paper: (16 lb. to 24 lb.)
Support Paper Size	11" x 17" to 8.5" x 11" / , 5.5" x 8.5" , 8" x 13"
Paper Capacity	Tray 3: Plain Paper: 500 sheets Thick Paper: 1/2/3: 150 Sheets
Power Requirements	Supplied from main unit
Max. Power Consumption	15 W or less
Dimensions (WxDxH)	23.63" x 27.75" x 11.75"
Weight Approx.	66.13 lb. (30 kg)

*There are six Foolscap sizes: 220 x 330 mm, 8.5"x 13", 8.5"x 13.5", 8.25"x 13", 8.125"x 13.25" and 8"x 13". Any of these sizes can be selected. For details, contact the technical representative.


PC-208 Paper Feed Cassette



Type	2 x 500 sheet universal drawers
Support Paper Type	Plain Paper: (16 lb. to 24 lb.)
Support Paper Size	11" x 17" to 8.5" x 11" / , 5.5" x 8.5" , 8" x 13"
Paper Capacity	Tray 3: Plain Paper: 500 sheets; Thick Paper 1/2/3: 150 Sheets Tray 4: Plain Paper: 500 sheets; Thick Paper 1/2/3: 150 Sheets
Power Requirements	Supplied from main unit
Max. Power Consumption	15 W or less
Dimensions (WxDxH)	23.63" x 27.75" x 11.75"
Weight Approx.	72.75 lb. (33 kg)

*There are six Foolscap sizes: 8.5"x 13.5", 220 x 330 mm, 8.5"x 13", 8.25"x 13" and 8.13"x 13.25", 8" x 13". Any of these sizes can be selected. For details, contact the technical representative.

PC-409 Large Capacity Cassette



Type	Large Capacity Cassette
Support Paper Type	Plain Paper: (16 lb. to 24 lb.)
Support Paper Size	8.5"x 11"
Paper Capacity	Plain Paper: 2,500 sheets
Power Requirements	Supplied from main unit
Max. Power Consumption	4.5 W or less
Dimensions (WxDxH)	23.63" x 27.75" x 11.75"
Weight Approx.	70.54 lb. (32 kg)


Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Component Considerations

DK-508 Copy Desk



Type	Storage drawer only
Function	Stores printing materials such as paper or toner. Required when no additional paper drawers are not installed, to bring the device to operational height
Dimensions (WxDxH)	23.63" x 27.75" x 11.75"
Weight Approx.	52.9 lb.

AU-102 Biometric Authentication Unit



Verification Time	Approx. 1 sec. or less
Interface	USB 2.0 (requires EK-604 or EK-605 Local USB Interface Kit and WT-506 Working Table; Can also be used with WT-507 Working Table (Side Panel Kit)
Dimensions (WxHxD)	2.3"(W) x 3.25"(D) x 2.9"(H)
Weight	0.19 lb. (not including USB cable)
Computer Requirements with PageScope Data Administrator	Processor, Memory, Hard Disk Drive, Monitor, Network, Application, Interface
Supported Operating Systems	Windows 2000 Professional (SP4) Windows XP Professional Edition (SP2) Windows Vista Business/Enterprise

AU-201H HID Card Authentication Unit



Dimensions (WxHxD)	3.63" x 2.5" x 0.63"
Weight	.25 lb.
Power Supply	Supplied from USB Port
System Conditions (operating mode)	Ambient Temperature: 32° to 104° F Humidity: 20% to 85%
System Conditions (non-operating mode)	Ambient Temperature: -4° to 122° F Humidity: 20% to 85%
Radio Law Division	Self-Guided Read-Write Communication Facility
Applicable Card	ISO 14443 Type A, FeliCa-based non-contact IC Card
Acquired Standard	VCCI Class B
Compatible Computer	CPU: PC/AT Compatible, 1 GHz or more Memory: 128MB or more HDD: 100MB or more free space Monitor: 800 x 600 pixels, 16-bit color or more Network: TCP/IP Application: Microsoft Internet Explorer 6.0 (SP1) or later Microsoft .NET Framework (SP1) or later
Supported Operating Systems	Windows 2000 Professional (SP4) Windows XP Professional Edition (SP2) Windows Vista Business/Enterprise

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Component Considerations continued

WT-506 Working Table



Type	External Table
Function	Holds AU-102 Biometric Authentication Unit or AU-201 HID Card Reader; Can be used as a place holder for originals and/or output.

EK-604 USB Host/Local Interface



Type	USB Interface and USB Cable.
Function	Required to connect External Keyboard

EK-605 USB Host/Local Interface + Bluetooth Interface



Type	USB Interface and USB Cable including the Bluetooth Board.
Function	Required to connect External Keyboard and provides Bluetooth printing capability.

MK-726 Mount Kit



Type	Internal Component
Function	Required to install FK-508 for each fax board installed.

LK-101 v2 License Kit

Type	License Key
Function	Web Browser (w/AJAX Support), Image Panel and Scan-to-SharePoint.

LK-102 License Kit

Type	License Key
Function	Enhanced PDF Encryption (128-bit AES Encryption).

LK-105 License Kit

Type	License Key
Function	Provides Searchable PDF functionality.

UK-203 i-Option Upgrade Kit



Type	1 GB Memory Upgrade (for i-Option License Kits)
Function	Required for LK-101 v2 Web Browser/Scan-to-Sharepoint/ Image Panel, LK-102 Enhanced PDF Encryption, LK-105 Searchable PDF and PageScope My Panel, (only one upgrade kit required per device).

SC-507 Copy Guard Kit

Type	Embedded Type
Function	Prevents printing of Copy Protected documents.

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Mixed Original Support

Document Size	Maximum Document Width					
	11" x 17" Landscape	8.5" x 11" Portrait	8.5" x 14" Landscape	8.5" x 11" Landscape	5.5" x 8.5" Portrait	5.5" x 8.5" Landscape
11" x 17"	●	●	×	×	×	×
8.5" x 11" (Portrait)	●	●	×	×	×	×
8.5" x 14"	●	●	●	×	×	×
8.5" x 11" (Landscape)	●	●	●	●	●	×
5.5" x 8.5" (Portrait)	×	×	●	●	●	×
5.5" x 8.5" (Landscape)	×	×	×	×	×	●

● Possible × Not Possible

Standard Paper Tray Support

Main Unit – bizhub 423/363/283/223 (Paper Tray 1 and 2)

Component	Capacity	Size	Weight
Tray 1	500 sheets	11" x 17"	16 lb. to 24 lb. bond
Tray 2	500 sheets	11" x 17"	16 lb. to 24 lb. bond
Bypass	150 sheets	11" x 17"	16 lb. to 55.75 lb. bond

Network Functions

Sending the Scanned Data in an Email Message

The scanned data can be sent to a specified Email address. The destination is specified from the touch panel of this machine and the scanned data is sent as an Email attachment.

Sending the Scanned Data as Files (FTP)

The scanned data is uploaded to a specified FTP server. The FTP server address, login password, and other information are entered from the touch panel of this machine. The data files uploaded to the FTP server can be downloaded from a computer on the network.

Sending the Scanned Data to a Computer on the Network (SMB)

The scanned data can be sent to a shared folder on a specified computer. The name of the destination computer, login password, and other information are entered from the touch panel of this machine.

Saving the Scanned Data in Boxes

The scanned data is uploaded to a specified web server. The host name, file path, user name, and password are entered on the touch panel of the machine. The data files uploaded to the server can be downloaded from a computer on the network.

Using the Machine as a Scanner

This machine can be used as a scanner. The scanner can be controlled from a PC connected to the network, and the scanned image can be loaded into an application on the PC to be processed.

Web Service (optional)

This machine can be used to access the Internet. Optional LK-101 v2 and UK-203 required.

PageScope Software

Network & Device Management	Management Tools
PageScope NetCare	bizhub vCare
Device Manager	
PageScope EMS Plug-Ins	Optional Software
PageScope Data Administrator	PageScope Enterprise Suite
Driver Packaging Utility	– PageScope Account Manager
HDD Back Up Utility	– PageScope Authentication Manager
Log Management Utility	– PageScope My Panel Manager
PageScope Download Manager	– PageScope My Print Manager
User Tools	
PageScope Direct Print	
PageScope Box Operator	
PageScope Print Status Notifier	
Font Management Utility	
Copy Protection Utility	
Print Utility for Unix	
PageScope Web Connection	

Security

Because information assets are critical, a company needs to effectively protect against the many security risks it faces.

- 1) Prevent Leaks of proprietary, confidential or personal information
- 2) Prevent unauthorized use of equipment
- 3) Effective data encryption
- 4) Protect data from being altered, duplicated or deleted
- 5) Prevent unauthorized access to data via the Internet
- 6) Protect against cyber attacks
- 7) Manage log history

Protective Functions: continued

- Copy Guard
- Password Copy
- Delete Graphic Data (when disposing of machine) HDD Sanitizing
- Delete Graphic Data (after each job) Job Erase
- Lock Job (when printing confidential documents)
- Protect data by requiring department name and 8-digit password
- Account Track
- HDD Lock

Protective Functions: continued

- Prevent Unauthorized Use
- Operation Log with 2,000-event memory
- HDD Encryption
- PDF Scan Encryption
- Enhanced PDF Scan Encryption
- Copy Protection
- Copy Guard (Optional)
- Network Authentication
- SMTP Authentication for Email
- SSL/TSL Compatibility for PS Web Connection, PS Data Administrator and LDAP Server
- Scan Data Encryption (TCP/socket SSL Compatibility)
- LDAP Authentication
- Box Operator Data Encryption
- Verification of Box Data Receipt
- IP Address Filtering
- Biometric Authentication Unit
- IP v6
- Encrypted Network Password Printing
- Scan-to-USB Memory with User Authentication
- Print-from-USB Memory with User Authentication
- S/MIME/Encryption

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Paper Considerations

Paper Size Conversion Chart

Paper	Letter	Letter R	Legal	Tabloid	Statement	Statement R
Measurement	8.5" x 11"	11" x 8.5"	8.5" x 14"	11" x 17"	5.5" x 8.5"	8.5" x 5.5"

Paper Weight Conversion Chart

gsm	Bond	Offset	Cover	Tag	Index	Point	Bristol	Caliper	
								inches	mm
60.20	16	40	22	37	33	3.2	27.4	0.0032	0.081
67.72	18	45	24	41	37	3.6	30.9	0.0036	0.092
75.20	20	50	28	46	42	3.8	34.3	0.0038	0.097
90.30	24	60	33	56	50	4.8	41.2	0.0048	0.120
105.35	28	70	39	64	58	5.8	48.1	0.0058	0.147
109.11	29	73	40	62	60	6.0	49.8	0.0060	0.152
116.63	31	81	45	73	66	6.1	53.2	0.0061	0.155
131.68	35	90	48	80	74	6.2	60.1	0.0062	0.157
135.45	36	90	50	82	75	6.8	61.8	0.0068	0.173
146.73	39	100	54	90	81	7.2	67.0	0.0072	0.183
150.50	40	100	56	93	83	7.3	68.7	0.0073	0.185
161.78	43	110	60	100	90	7.4	73.8	0.0074	0.188
165.55	44	110	61	02	92	7.6	75.5	0.0076	0.193
176.83	47	120	65	108	97	8.0	80.7	0.0078	0.198
199.41	53	135	74	122	110	9.0	91.0	0.0085	0.216
203.17	54	137	75	125	113	9.0	92.7	0.0090	0.229
218.22	58	146	80	134	120	9.5	99.6	0.0092	0.234
244.56	65	165	90	50	135	10.0	111.6	0.0095	0.241
252.08	67	170	93	156	140	10.5	115.1	0.0100	0.250
270.90	72	183	100	166	150	11.0	123.7	0.0110	0.289
285.95	76	192	105	175	158	13.0	130.5	0.0130	0.330
308.52	82	208	114	189	170	14.0	140.8	0.0140	0.356
312.00	87	220	120	200	180	15.0	142.4	0.0150	0.380
385.06	105	267	146	244	220	18.0	175.8	0.0175	0.445

Recommended Paper Stocks (Please log on to mykonicaminolta.com for updates on paper recommendations.)

Class.	Weight	Brand of Paper	Size
Plain Paper	20 lb. Bond (75 g/m ²)	Hammermill Tidal MP	8.5" x 11"
Plain Paper	20 lb. Bond (75 g/m ²)	Domtar Recycled Husky	8.5" X 11"
Plain Paper	20 lb. Bond (75 g/m ²)	Xerocopy (with 30% Post-consumer content)	8.5" X 11"
Thick	32 lb. Cover (120 g/m ²)	Hammermill ¹ Color Copy	8.5" X 11"
Thick	60 lb. Cover (163 g/m ²)	Hammermill ¹ Color Copy	8.5" X 11"
Thick	80 lb. Cover (216 g/m ²)	Hammermill ¹ Color Copy	8.5" X 11"
OHP Transparencies	—	3M PP2500 Plain Paper Copier Transparency Film	8.5" X 11"
Envelope	24 lb.	Preservation Wove 50% Recycled/ 30% Post-Consumer, #6-3/4 – 24# Wove Envelopes #57859	3.85" x 6.46"

^{*1} Hammermill Color Copy Paper 80lb is not guaranteed referring to image quality standards.

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



How to Build a bizhub 423/363/283/223 System (from start to finish)

Step 1: Base Unit

- 423/363/283/223
Digital Printer/Copier/Scanner/Fax
(Includes PS, PCL & XPS Controller, 2 GB Standard Memory, Duplex Unit, USB Interfaces for Scan-to-USB Thumb Drive/Print-from-USB Thumb Drive, USB Local Printing, Optional Authentication Device Connection, Service USB Firmware Updates)

Step 2: Document Handling Options (Select one)

- ☐ OC-509 Original Cover
- ☐ DF-621 Reversing Automatic Document Feeder
(Standard on bizhub 423/363)

Step 3: Paper Supply/Cabinet Options (Required)

Select one of the following:

- ☐ PC-409 Large Capacity Cassette
(2,500 sheets - Letter crosswise only)
- ☐ PC-208 2-way Paper Feed Cassette
(Two 500-sheet Universal Cassettes)
- ☐ PC-109 Paper Feed Cassette
(One 500-sheet Universal Cassette; Includes 1 storage drawer)
- ☐ DK-508 Copy Desk (Storage Drawer Only)

Step 4: Output Options

- ☐ None
- ☐ JS-505 Job Separator Tray
- ☐ FS-527 Floor Finisher (50-sheet stapling)
 - ☐ JS-603 Job Separator Tray
(3rd Output Tray for FS-527)
 - ☐ PK-517 Punch Kit (for FS-527)
 - ☐ SD-509 Saddle Stitcher Kit (for FS-527)
- ☐ FS-529 Inner Finisher (50-sheet stapling)

Step 5: Analog Fax Options


- ☐ FK-508 Fax Kit
- ☐ MK-726 Mount Kit
- ☐ SP-501 Stamp Unit
(for DF-621)
- ☐ Spare TX Marker Stamp 2

Step 6: Controller Option

- Standard Controller (PCL/PS/XPS)
- ☐ HD-516 250 GB Hard Disk Drive
(Standard on bizhub 423/363)

Step 7: Additional Options

- ☐ AU-102 Biometric Authentication Unit
(Requires WT-506)
- ☐ AU-201H HID Proximity Card Authentication Unit
(WT-506 recommended)
- ☐ AU-202H HID iClass Card Authentication Unit
(Requires WT-506)
- ☐ AU-211P CAC/PIV Card Authentication Unit
(Requires WT-506)
- ☐ EK-604 USB Connection Kit
(For External Keyboard)
- ☐ EK-605 USB Connection Kit
(For External Keyboard and Bluetooth Printing)
- ☐ External USB Keyboard (Requires KH-101)
 - ☐ KH-101 Keyboard Holder
- ☐ LK-101 v2 License Kit (Web Browser, Image Panel and Scan-to-SharePoint)
- ☐ LK-102 License Kit (Enhanced PDF Encryption)
- ☐ LK-105 License Kit (Searchable PDF)
- ☐ SC-507 Copy Guard Kit
- ☐ UK-203 Memory Upgrade Kit (Required for LK-101 v2, LK-102, LK-105 and PageScope My Panel; only one memory upgrade required on MFP)
- ☐ WT-506 Working Table



Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



KONICA MINOLTA

Accessory Options for bizhub 423/363/283/223 Full Color Printer/Copier/Scanner

ACCESSORIES	ITEM NO.	DESCRIPTION	NOTES
BASE UNIT			
423	A1UD011	bizhub 423 Monochrome Printer/Copier/Color Scanner/Fax	Includes DF-621 RADF, PS, PCL & XPS Emperon Controller, 2 GB Memory, HD-516 250 GB HDD, USB Interface for Print to and Scan from USB Memory, USB Local Printing, Optional Authentication Device Connection, Service USB Firmware Connection, Developer and Drum.
363	A1UE011	bizhub 363 Monochrome Printer/Copier/Color Scanner/Fax	Includes DF-621 RADF, PS, PCL & XPS Emperon Controller, 2 GB Memory, HD-516 250 GB HDD, USB Interface for Print to and Scan from USB Memory, USB Local Printing, Optional Authentication Device Connection, Service USB Firmware Connection, Developer and Drum.
283	A1UF011	bizhub 283 Monochrome Printer/Copier/Color Scanner/Fax	Includes PS, PCL & XPS Emperon Controller, 2 GB Memory, USB Interface for Print to and Scan from USB Memory, USB Local Printing, Optional Authentication Device Connection, Service USB Firmware Connection, Developer and Drum. Note: DF-621 RADF and HD-516 250 GB HDD are optional.
223	A1UG011	bizhub 223 Monochrome Printer/Copier/Color Scanner/Fax	Includes PS, PCL & XPS Emperon Controller, 2 GB Memory, USB Interface for Print to and Scan from USB Memory, USB Local Printing, Optional Authentication Device Connection, Service USB Firmware Connection, Developer and Drum. Note: DF-621 RADF and HD-516 250 GB HDD are optional.
DOCUMENT HANDLING OPTION			
OC-509	A128WY2	Original Cover	Required if DF-621 is not installed.
DF-621	A143WY1	Reversing Automatic Document Feeder	100-Sheet Reversing Automatic Document Feeder; Standard: bizhub 423/363 Option: bizhub 283/223
PAPER SUPPLY/ CABINET OPTIONS			
PC-409	A1V4W13	Large Capacity Cassette	2,500 sheets; Letter-Size (Portrait) Paper only.
PC-208	A1V4WY2	2-Way Paper Feed Cabinet	Two 500-sheet Universal Paper Cassettes.
PC-109	A1V4WY1	Paper Feed Cabinet	One 500-sheet Universal Paper Cassette and Storage Drawer.
DK-508	A1V4WY4	Copy Desk	Storage Drawer only.
OUTPUT OPTIONS			
None			
JS-505	A083WY2	Job Separator Tray	Separates print, copy and fax jobs; can be installed if finisher is not attached.
FS-527	A0HRWY2	Floor Finisher	50-sheet staple finisher required to support additional Output Tray, Punch Kit and Saddle Stitcher.
FS-529	A0U7WY2	Inner Finisher	Provides 50-sheet stapling.
JS-603	A10FWY1	Job Separator Tray (3rd Output tray for FS-527)	Adds third tray to FS-527 Finisher.
PK-517	A10EW11	2/3-Hole Punch Kit for FS-527	2/3-Hole Punch Kit for FS-527.
SD-509	A10DWY1	Saddle Stitcher Kit for FS-527	Provides booklet output for FS-527.
ANALOG FAX OPTIONS			
FK-508	A22M011	Fax Board	Adds Super G3 fax functionality, IP Address Fax, PC Network Fax. Up to two Fax Boards can be installed for multi-line fax configurations.
MK-726	A2A0WY0	Fax Mount Kit	Required for FK-508 for each fax board installed.
SP-501	4614506	Fax Stamp Unit	Installed on RADF.
Spare TX Marker Stamp 2	4614511	Spare TX Marker Stamp	Installed on RADF.
CONTROLLER OPTION			
HD-516	A2ACWY1	250 GB Hard Disk Drive	Standard: bizhub 423/363 Option: bizhub 283/223
ADDITIONAL OPTIONS			
AU-102	A0X9WY1	Biometric Authentication Unit	Also compatible with bizhub C652 series and C360 series. Requires WT-506 Working Table.
AU-201H	7640005064	HID Proximity Card Authentication Unit	WT-506 Working Table recommended. If WT-506 Working Table is not installed, AU-201H must be mounted to device.
AU-202H	7640008354	HID iClass Card Authentication Unit	Requires WT-506 Working Table.
AU-211P	7640008082	CAC/PIV Card Authentication Unit	Requires WT-506 Working Table.

Konica Minolta bizhub 423/363/283/223

Specification & Installation Guide



Accessory Options for bizhub 423/363/283/223 Full Color Printer/Copier/Scanner

ADDITIONAL OPTIONS *continued*

ACCESSORIES	ITEM NO.	DESCRIPTION	NOTES
EK-604	A0YCWY4	USB Connection Kit	Required for External Keyboard (either EK-604 or EK-605 required to support External Keyboard).
EK-605	A0YCWY3	USB Connection Kit w/Bluetooth Printing	Required for External Keyboard (either EK-604 or EK-605) and Bluetooth Printing for mobile phone/PDA.
LK-101 v2	A0PD01A	i-Option License Kit	Enables Web Browser from the MFP Control Panel, Image Panel (move, combine, restore user files at the MFP) and Scan-to-SharePoint functions. Requires UK-203.
LK-102	A0PD012	i-Option License Kit	Enables 128-bit AES PDF encryption; Apply digital IDs and signatures. Requires UK-203.
LK-105	A0PD015	i-Option License Kit	Enables Searchable PDF functionality . Requires UK-203.
External Keyboard	7640006869	External USB Keyboard	Computer type keyboard for alphanumeric data entry (alternative to the standard QWERTY keyboard available on the MFP's LCD); Requires either EK-604 or EK-605 and KH-101.
KH-101	A165WY1	Keyboard Holder	Holds the optional QWERTY keyboard in place on the MFP.
SC-507	A0Y9WY1	Copy Guard Kit (Copy Guard/Password Copy Protection)	Detects documents with copy patterns applied. Gives users the option to prevent copying sensitive documents or allows copying when password is entered.
UK-203	A0YDWY1	i-Option Memory Upgrade Kit	Required for LK-101 v2, LK-102, LK-105 and PageScope My Panel; Contents include 1 GB memory upgrade. Only one UK-203 required per machine.
WT-506	A0W4WY1	Working Table	Required for AU-102 Biometrics Authentication Unit and recommended for AU-201H HID Card Authentication Unit. Also compatible with bizhub C652 series and C360 series.
Key Counter Mount Kit 1	4623472	Key Counter Kit	Compatible with bizhub C353 series, C360 series and C650 series.

CONSUMABLE YIELDS*

CONSUMABLE	ITEM NO.	YIELD
TN-414 Toner for bizhub 423/363	A202030	25,000 pages
TN-217 Toner for bizhub 283/223	A202031	17,500 pages
DR-411 Drum	A2A103D	(bizhub 423) 121,000 pages (bizhub 363) 110,000 pages (bizhub 283) 100,000 pages (bizhub 223) 80,000 pages
DV-411 Developer	A202500	(bizhub 423) 121,000 pages (bizhub 363) 110,000 pages (bizhub 283) 100,000 pages (bizhub 223) 80,000 pages
Staples SK-602 (For FS-527, FS-529 and SD-509)	14YK	5,000 x 3 pkg/case

* Based on 6% total coverage